08/2018



Marine & Offshove Division



Certificate number: 17330/C0 EC File number: ACI 3000/005/005

Annex A1 Item number: A.1/3.7 This certificate is not valid when presented without the full

attached schedule composed of 7 sections www.veristar.com

Notified Body 0062 - MARINE EQUIPMENT DIRECTIVE 96/98/EC

EC TYPE EXAMINATION CERTIFICATE

as per Module B of European Union Council Directive 96/98/EC on marine equipment as amended by Commission Directive 2013/52/EU

This certificate is issued to

HONEYWELL RESPIRATORY SAFETY PRODUCTS SAS

ROISSY CDG cedex - FRANCE

for the type of product

SELF-CONTAINED COMPRESSED-AIR-OPERATED BREATHING APPARATUS

FENZY X-PRO type 2 Model

(Mono or Bi version - minimum capacity 1200l) complete with their full face mask.

Requirements:

SOLAS 74 convention as amended, Regulations II-2/10, X/3

IMO Res. MSC.36(63) -(1994 HSC Code)- as amended, 7

IMO Res. MSC,97(73) -(2000 HSC Code)- as amended, 7 IMO Res. MSC,98(73)-(FSS Code)- as amended by MSC.206(81), MSC.217(82), MSC.292(87), MSC.311(88), MSC.327(90) and MSC.339(91),/3

EN 136:1998/incl. /AC:2003, EN 137:2006

And where the apparatus is for use in accidents with cargo:

IMO Res. MSC.4(48)-(IBC Code)- as amended, 14,

IMO Res. MSC.5(48)-(IGC Code)- as amended, 14

ISO 23269-3:2011

This certificate is issued on behalf of the French Maritime Authorities to attest that BUREAU VERITAS did undertake the relevant type examination procedures for the product identified above which was found to comply with the relevant requirements of the Council Directive 96/98/EC of 20 December 1996 as amended.

This certificate will expire on: 21 May 2020

For BUREAU VERITAS Notified Body 0062,

A BV LA ROCHELLE, on 21 May 2015,

Hatrice DAVID



de la Legitimación asentada con el N.º 24/26

This certificate does not allow to issue the Declaration of Conformity and to affix the mark of conformity (wheelmark 🏶) to the products corresponding to this type. To this end, the production-control phase module (D, E or F) of Annex B of the Directive is to be complied with and controlled by a writte inspection agreement with a notified body.

This certificate remains valid until the date stated above, unless cancelled or revoked, provided the conditions indicated in the subsequent page(s) are complied with In the product remains valid until the date stated above, unless cancelled or revoked, provided the conditions indicated in the subsequent page(s) are complied with and the product remains satisfactory in service. This certificate will not be valid if the applicant makes any changes or modifications to the approved product, which have not been notified to, and agreed in writing with BUREAU VERITAS. Should the specified regulations or standards be amended during the validity of this certificate, the product(s) is/are to be re-approved prior to it/they being placed on board vessels to which the amended regulations or standards apply. BUREAU VERITAS is designated by the French Maritime Authority as a "notified body" under the terms of the French Regulations Division 140 Chapter 140-2. This certificate is issued within the scope of the General Conditions of BUREAU VERITAS Marine & Offshore Division available on the internet site www.veristar.com. Any Person not a party to the contract pursuant to which this document is delivered may not assert a claim against BUREAU VERITAS for any liability arising out of errors or omissions which may be contained in said document, or for errors of judgment, fault or negligence committed by personnel of the Society or of its Agents in establishment or issuance of this indeximent and in connection with any activities for which it may received. establishment or issuance of this document, and in connection with any activities for which it may provide.

MANUDEN

Certificate number: 17330/C0 EC

THE SCHEDULE OF APPROVAL

1. PRODUCT DESCRIPTION:

The FENZY X-PRO type 2 is a Self-Contained open-circuit positive pressure Breathing Apparatus -SCBA- with full face mask, operating on compressed air.

The FENZY X-PRO range uses air compressed in high pressure cylinder(s) (the apparatus is designed for 200 or 300 bar using one or two pressure cylinders) carried out on an anatomic back-pack equipped with engulfment resistance and adjustable straps.

Connection of the reducer to the cylinder valve can be obtained by a 200/300 bar hand tight coupling (screw or quick connector)

The FENZY X-PRO type 2 consists of:

- full face mask (PANORAMA, OPTI-PRO and OPTI-PRO with communication system)
- compressed air cylinder
- cylinder valve
- back-pack with body harness
- high/medium pressure reducer
- lung governed demand valve (SA 5000, SA 5000 ZENITH or SX-PRO)
- pressure indicator
- medium pressure hose
- high/medium pressure hose with a pneumatic or an electronic pressure indicator (FENZY ANGEL II),

In compliance with EN 137 the weight of all equipment is not more than 18 kg.

The dimensions are Height 670 mm x Length 240 mm x Breadth 240 mm.

An automatic warning whistle is located on the pressure reducer unit, warning the wearer that the remaining pressure in the pressure vessel(s) is low.

The apparatus is to be used with a complete face mask Class 3 complying with standard EN 136.

As per requirements of regulations stated on the front page of this certificate, the volume of air contained in the cylinders shall be at least 1200 litres.

Different versions of FENZY X-PRO, indicated in the configuration table N° P/N 022-13-R&D-APAVE-01 (for 89/686/CE directive and 98/96/CE directive) and the EC configuration table N° 007-05-ING-DESP-08 (for PED 97/23/EC directive), are possible, depending on :

- type of compressed air cylinder(s),
- type of air cylinder valve(s),
- the type of harness,
- type of demand valve (SX-PRO, SA5000 or SA5000 Zenith),
- type of face mask (PANORAMASQUE or OPTI-PRO)
- type of second user,
- the type of medium pressure hose,
- the type high/medium pressure hose with a pneumatic or an electronic pressure indicator (FENZY ANGEL II)
- the type second user MP device (inlet or outlet connection)

Their codification is the name of the apparatus, FENZY X-PRO type II.

Only approved flexible hoses (HP and MP) can be used with the FENZY X-PRO type II.

The air supply shall meet the requirements for breathable air according to EN 12021.

2. DOCUMENTS AND DRAWINGS:

2.1 - Design drawings and specifications

Reference are included in the manufacturer documentation N°P/N 022-13-R&D-APAVE-01 and N° 007-05-ING-DESP-08.

2.2 - Manual for installation, use and maintenance given in documentation in §2.1





3.1 - Test report in compliance with EN 136:1998 and EN 137:2006:

Test report N°14.7.0045.002.1, dated 03/07/2014, N° 14.7.D107.002.1 dated 12/12/2014, from APAVE Testing Center, France.

3.2 - Test report in compliance with ISO 23269-2 (2011) called by ISO 23269-3 (2011):

Test reports N°P122869 - Document DE/3, dated 29/07/2014, N°P122869 - Document DE/4, dated 29/07/2014, and N°P132070 - document DE/2 dated 27/01/2015 and N°P132070 - document DE/3 dated 12/02/2015, all from LNE Laboratories, France.

Test report N°14.7.0023.002.1, dated 03/07/2014 and 15.7.0020.001.1 dated 13/03/2015, from APAVE Testing Center, France.

3.3 - Test report in compliance with ISO 23269-3 (2011):

Test report N°8148/14, dated 30/06/2014, from DEKRA EXAM GmbH, Germany.

4. APPLICATION / LIMITATION:

4.1 - Air cylinder(s)

Depending on type, the equipment is fitted with one (mono) or two (twin) air pressure cylinder(s). The compressed air pressure cylinder(s) must comply with Pressure Equipment Directive 97/23/EC as amended and are to be marked accordingly.

4.2 - Reducers

Only the reducer described in the manufacturer documentation N° P/N 022-13-R&D-APAVE-01 and N° 007-05-ING-DESP-08 can be used with FENZY X-PRO.

- 4.3 Full face masks are not suitable for persons bearing beard or moustache.
- 4.4 Allowed combinations of air pressure vessel(s), reducer and full face mask are to be as per test reports listed in section 3
- 4.5 Service life: as per manufacturer's instructions and in conformity with applicable rules.
- 4.6 The equipment is to be stored and maintained on board according to manufacturer's instructions and applicable rules.
- 4.7 The equipment shall be serviced only by approved Servicing Stations.
- 4.8 On board the ship, the equipment is to be provided with a fireproof lifeline of sufficient length and strength as per FSS Code, Chapter 3, regulation 2.1.3 (also in 2000 HSC Code, Chapter 7, regulation 7.10.3.3), either capable of being attached to the back plate of the device.
- 4.9 Manufacturer's instructions (see 2.2 above) should accompany every apparatus on delivery and should be kept on board.
- 4.10 As per FSS Code, Chapter 3, regulation 2.1.2 and 2000 HSC Code, Chapter 7, regulation 7.10.3.2.2, the volume of air contained in the cylinders shall be at least 1200 litres or the apparatus shall be capable of functioning for at least 30 minutes. It shall be taken into account when referring to manufacturer documentation N° P/N 022-13-R&D-APAVE-01 and N° 007-05-ING-DESP-08.

5. PRODUCTION SURVEY REQUIREMENTS:

This certificate alone does not allow the applicant to issue the Declaration of Conformity and to affix the mark of conformity (wheelmark) to the products corresponding to this type. To this end, the production-control phase module D "Production Quality Assurance" or E "Product Quality Assurance" or F "Product Verification" of Annex B of the Directive is to be complied with and controlled by a written inspection agreement with a Notified Body.

The electronic version is available at: http://www.veristarpm.com/veristarnb/jsp/viewPublicPdfTypec.jsp?id=ukbtdhkacc BV Mod. Ad.E 536 December 2014

This certificate consists of 4 page(s)

Certificate number: 17330/C0 EC

6. MARKING OF PRODUCT:

- 6.1 The apparatus is to be marked in accordance with provisions of EN 136:1998, EN 137:2006, and ISO 23269-3 (2011).
- 6.2 Markings as per MED 96/98/EC:
- X YYYY/XX where YYYY is the number of the Notified Body undertaking surveillance module (when BV, 0062) and where XX are the last two digits of year mark affixed.

7. OTHERS:

- 7.1 This approval is given with the understanding that the manufacturer will accept full responsibility for informing shipbuilders or their sub-contractors of the proper methods of fitting and general maintenance of the approved equipment and the conditions of this approval.
- 7.2 This certificate supersedes the type approval certificate N° 17330/B2 EC previously issued by the Society.

*** END OF CERTIFICATE ***



08/2018



ALMUDENA CASTRO-GIRONA MARTÍNEZ, Notario del Ilustre Colegio de CATALUNYA con residencia en CASTELLBISBAL, DOY FE: Que el documento que antecede es TESTIMONIO LITERAL de su original con el que concuerda. Y a instancia de AIRBOX S.A. lo expido en tres folios de papel de uso exclusivamente notarial, el presente y los dos siguientes en orden correlativo de la misma serie.

Asiento nº 24 de la Sección Segunda del Libro Indicador.

En CASTELLBISBAL a quince de enero de dos mil diecinueve. DOY FE.











10/2018



El presente folio es el agregado al documento en el que figura la firma de Doña Almudena Elena Castro-Girona Martínez, Notario de Castellbisbal, Colegio Notarial de Cataluña, en testimonio de exhibición de certificado, a instancia de AIRBOX, S.A., libro indicador 24, de 15 de enero de 2019, en el folio EJ5327399.

APOSTILLE (Convention de La Haye du 5 octobre 1961) 1. País: **ESPAÑA** Country / Pays: El presente documento público This public document / Le présent acte public 2. ha sido firmado por Doña Almudena Elena Castro-Girona Martínez has been signed by a été signé par quien actúa en calidad de Notario acting in the capacity of agissant en qualité de y está revestido del sello / timbre de la Notaría bears the seal / stamp of est revêtu du sceau / timbre de Certificado Certified / Attesté 5. en Barcelona 6. el día 17/01/2019 at / à 7. por Don José Alberto Marín Sánchez, Vicedecano del Colegio Notarial de Cataluña by / par 8. bajo el número N5301/2019/002340 No FE PUBLICA sous no OTARIAL 9. Sello / timb 10. Firma: Seal / stamp: Signature: Sceau / timbi Signature : VIHIL PRIUS José Alberto Marín Sánchez. Vicedecano

Esta Apostilla certifica únicamente la autenticidad de la firma, la calidad en que el signatario del documento haya actuado y, en su caso, la identidad del sello o timbre del que el documento público esté revestido.

Esta Apostilla no certifica el contenido del documento para el cual se expidió.

[No es válido el uso de esta Apostilla en España]

[Esta Apostilla se puede verificar en la dirección siguiente: https://sede.mjusticia.gob.es/eregister]
Códígo de verificación de la Apostilla: NA:7ig0-l3Nz-4WzA-fFNC

This Apostille only certifies the authenticity of the signature and the capacity of the person who has signed the public document, and, where appropriate, the identity of the seal or stamp which the public document bears.

This Apostille does not certify the content of the document for which it was issued.

[This Apostille is not valid for use anywhere within Spain]

To verify the issuance of this Apostille, see https://sede.mjusticia.gob.es/eregister]

Verification Code of the Apostille:NA:7ig0-l3Nz-4WzA-fFNC

Cette Apostille atteste uniquement la véracité de la signature, la qualité en laquelle le signataire de l'acte a agi et, le cas échéant,

l'identité du sœau ou timbre dont cet acte public est revêtu. Cette Apostille ne certifie pas le contenu de l'acte pour lequel elle a été émise.

[L'utilisation de cette Apostille n'est pas valable en / au Espagne.]

[Cette Apostille peut être vérifiée à l'adresse suivante https://sede.mjusticia.gob.es/eregister]

Code de verification de l'Apostille:NA:7ig0-l3Nz-4WzA-fFNC

a CATAL,